# **MAN TGX 18.460 4X2 BLS**

# SH01870825



Price

21,990 EUR (net)

**26,608 EUR** (gross)

Offer Date

18.10.2025

Body type Tractor unit 03/2019 1st req.

Power 338kW (460 HP) Mileage 533454 km

Storage location Otopeni - MHS Truck

Service

# **BASIC DATA**

Brand MAN Model serie **TGX** 

Model variant TGX TG2

Body type Tractor unit (Standard)

Colours white XL Driver's cab Berths 1 berth

# **TECHNICAL DATA**

Power 338 kW (460 HP)

Fuel Diesel

Gearbox type **Automatic** 

4x2 Wheel drive

Suspension Leaf air suspension

Axles 2 axles

# **WEIGHTS AND MEASURES**

GVW 18,000 kg

Rear overhang 800 mm Wheel base 3600 mm

Fuel tank AdBlue: 60 I

Fuel tank: 580 I

Emission category Euro6



# **EQUIPMENT**

# Safety

- Antilock Braking System ABS
- Anti Slip Regulation ASR
- Electr. Stability Programm ESP
- Immobilizer
- Rear underrun
- Kerb mirror: right
- Heated wide angle mirror

### Interior

- Board computer
- Multifunctional steering wheel
- Aluminum inlays
- Digital tachograph
- Carpet floor covering
- Cooling box

### **Audio & communication**

Radio

#### **Exterior**

- Electr. and heated rear view mirrors
- Low noise
- Rear differential lock
- PTO
- Fifth wheel
- 1x15 pin plug
- Cab Suspension

#### Comfort

- Adjustable steering column
- Electric window lift 2x
- Air conditioning
- Comfortable driver seat
- Additional heating
- Central locking with remote control
- Air-suspended driver seat
- Cup holder front
- Isolated driver's cab
- DC/AC converter

# **Light and sight**

- Fog lights
- Tinted glass
- Headlight range control
- Cornering light
- Daytime running lights

# **Assistance systems**

- Cruise control
- MAN BrakeMatic
- Brake assist: Emergency Brake Assist 2
- Lane-Guard-System LGS
- Speed limiter



- Axle load indicator
- Lifting roof (manual)
- RIO Box

# Wheels and tyres

Spare wheel carrier

# **Others**

front springs parabolic 7.5 t, rear air suspension 13 t, hub reduction rear axle Hypoid HY-1350, HY axle ratio i 2.71, fuel filter heating, cab insulation NORDIC, trailer socket 24V (15-pin)