

# MAN TGX 18.460 4X2 BLS

SHV001725



Price **30,990 EUR** (net)  
**37,498 EUR** (gross)  
Offer Date 27.08.2025

Body type	Tractor unit
1st reg.	05/2019
Power	338kW (460 HP)
Mileage	212883 km
Storage location	Otopeni - MHS Truck Service

## BASIC DATA

Brand	MAN
Model serie	TGX
Model variant	TGX TG2
Body type	Tractor unit (Standard)
Colours	white
Driver's cab	XL
Berths	1 berth

## TECHNICAL DATA

Power	338 kW (460 HP)
Fuel	Diesel
Gearbox type	Manual
Wheel drive	4x2
Suspension	Leaf air suspension
Axles	2 axles

## WEIGHTS AND MEASURES

GVW	18,000 kg
Rear overhang	750 mm
Wheel base	3600 mm
Fuel tank	AdBlue: 60 l Fuel tank: 400 l
Emission category	Euro6

## EQUIPMENT

### Safety

- Antilock Braking System ABS
- Anti Slip Regulation ASR
- Immobilizer
- Kerb mirror: right
- Heated wide angle mirror

### Comfort

- Adjustable steering column
- Electric window lift 2x
- Air conditioning
- Driver's armrest
- Comfortable driver seat
- Additional heating
- Central locking with remote control
- Air-suspended driver seat
- Cup holder front
- Isolated driver's cab
- DC/AC converter

### Interior

- Board computer
- Multifunctional steering wheel
- Aluminum inlays
- Digital tachograph
- Sun visor
- Carpet floor covering

### Audio & communication

- Radio
- Mobile phone preparation Bluetooth
- AUX & USB connector

### Assistance systems

- Cruise control
- MAN BrakeMatic
- Speed limiter

### Light and sight

- Tinted glass
- Headlight range control
- Daytime running lights

### Exterior

- Electr. and heated rear view mirrors
- Low noise
- Rear differential lock
- PTO: PTO NH/1C without flange  
f0.91/1.09right side, horizontal
- Fifth wheel

- 1x15 pin plug
- Cab Suspension
- Working lights
- Lifting roof (manual)
- RIO Box

### Wheels and tyres

- Spare wheel carrier

### Others

- front springs parabolic 8.0 t, rear air suspension 13 t, hub reduction rear axle AP HP-1352, planetary axle ratio i 3.63, fuel filter heating, cab insulation NORDIC, wiring for tank truck to ADR, ADR Typ AT, trailer socket 24V (15-pin), pick-up plate 40 mm