# MAN

# **MAN TGX 18.440 4X2 BLS**

### SH04580524



Price

**11,990 EUR** (net)

**14,508 EUR** (gross)

Offer Date

14.08.2025

Body type

1st reg. 04/2016

Power 324kW (441 HP)

Mileage 776087 km

Storage location Otopeni - MHS Truck

Service

Tractor unit

# **BASIC DATA**

Brand MAN

Model serie TGS

Model variant TGS TG2

Body type Tractor unit (Standard)

Colours white

Driver's cab XL

Berths 1 berth

# **TECHNICAL DATA**

Power 324 kW (441 HP)

Fuel Diesel

Gearbox type Manual

Wheel drive 4x2

Suspension Leaf air suspension

Axles 2 axles

## **WEIGHTS AND MEASURES**

GVW 18,000 kg

Rear overhang 750 mm

Wheel base 3600 mm

Fuel tank AdBlue: 60 I

Fuel tank: 400 l

Emission category Euro6



# **EQUIPMENT**

#### Safety

- Antilock Braking System ABS
- Anti Slip Regulation ASR
- Immobilizer
- Kerb mirror: right
- Heated wide angle mirror

#### Interior

- Board computer
- Multifunctional steering wheel
- Digital tachograph
- Carpet floor covering

#### **Audio & communication**

- Radio/CD
- AUX & USB connector

#### Light and sight

- Tinted glass
- Headlight range control
- Daytime running lights

#### **Others**

#### Comfort

- Adjustable steering column
- Electric window lift 2x
- Air conditioning
- Driver's armrest
- Comfortable driver seat
- Central locking with remote control
- Air-suspended driver seat
- Isolated driver's cab
- DC/AC converter

#### **Exterior**

- Self-levelling suspension
- Electr. and heated rear view mirrors
- Low noise
- Rear differential lock
- PTO: PTO NH/1C without flange f0.91/1.09right side, horizontal
- Fifth wheel
- Lifting roof (manual)

#### **Assistance systems**

- Cruise control
- MAN BrakeMatic
- Speed limiter

#### Wheels and tyres

Spare wheel carrier



front springs parabolic 8.0 t, rear air suspension 13 t, hub reduction rear axle AP HP-1352, planetary axle ratio i 3.63, fuel filter heating, cab insulation NORDIC, wiring for tank truck to ADR, ADR Typ AT, equipment for dangerous goods to ADR, type OX, supply kit for semitrailer with lifting axle or moving-off aid, trailer socket 24V (7-7-pin), pick-up plate 40 mm