

MAN TGX 18.440 4X2 BLS

SH05820924



Price **15,400 EUR** (net)

18,634 EUR (gross)

Offer Date 06.08.2025

Body type	Tractor unit
1st reg.	10/2015
Power	324kW (441 HP)
Mileage	797574 km
Storage location	Otopeni - MHS Truck Service

BASIC DATA

Brand	MAN
Model serie	TGS
Model variant	TGS TG2
Body type	Tractor unit (Standard)
Colours	white
Driver's cab	XLX
Berths	1 berth

TECHNICAL DATA

Power	324 kW (441 HP)
Fuel	Diesel
Gearbox type	Manual
Wheel drive	4x2
Suspension	Leaf air suspension
Axles	2 axles

WEIGHTS AND MEASURES

GVW	18,000 kg
Rear overhang	800 mm
Wheel base	3600 mm
Fuel tank	AdBlue: 60 l Fuel tank: 400 l
Emission category	Euro6

EQUIPMENT

Safety

- Antilock Braking System ABS
- Anti Slip Regulation ASR
- Electr. Stability Programm ESP
- Immobilizer
- Rear underrun
- Kerb mirror: right
- Heated wide angle mirror

Interior

- Board computer
- Multifunctional steering wheel
- Digital tachograph
- Sun visor
- Carpet floor covering

Audio & communication

- Radio/CD
- AUX & USB connector

Light and sight

- Tinted glass
- Headlight range control

Comfort

- Adjustable steering column
- Electric window lift 2x
- Automatic climate control
- Driver's armrest
- Comfortable driver seat
- Additional heating
- Central locking with remote control
- Air-suspended driver seat
- Isolated driver's cab
- DC/AC converter

Exterior

- Self-levelling suspension
- Electr. and heated rear view mirrors
- Roof spoiler
- Low noise
- Rear differential lock
- PTO
- Fifth wheel
- Spare wheel
- Cab Suspension
- Lifting roof (manual)
- Telematics system

Assistance systems

- Cruise control
- MAN BrakeMatic
- Speed limiter

■ Daytime running lights

Wheels and tyres

■ Spare wheel carrier

Others

■ front springs parabolic 7.5 t, rear air suspension 13 t, hub reduction rear axle Hypoid HY-1350, HY axle ratio i 2.71, fuel filter heating, cab insulation NORDIC, wiring for tank truck to ADR, ADR Typ AT, equipment for dangerous goods to ADR, type OX, supply kit for semitrailer with lifting axle or moving-off aid, trailer socket 24V (7-7-pin), pick-up plate 40 mm