

MAN TGX 18.440 4X2 BLS



Price

Offer Date

12,500 EUR (net) **15,125 EUR** (gross) 06.08.2025

Tractor unit 04/2015 324kW (441 HP) 987313 km Braşov - MHS Truck Service

BASIC DATA

Brand	MAN
Model serie	TGX
Model variant	TGX TG2
Body type	Tractor unit (Standard)
Colours	white
Driver's cab	XLX
Berths	2 berths

TECHNICAL DATA

Power	324 kW (441 HP)
Fuel	Diesel
Gearbox type	Automatic
Wheel drive	4x2
Suspension	Leaf air suspension
Axles	2 axles

WEIGHTS AND MEASURES

GVW	18,000 kg
Rear overhang	800 mm
Wheel base	3600 mm
Fuel tank	AdBlue: 60 I
	Fuel tank: 580 l
	Fuel tank: 580 l
Emission category	Euro6

SHV00011223



EQUIPMENT

Safety

- Antilock Braking System ABS
- Anti Slip Regulation ASR
- Electr. Stability Programm ESP
- Immobilizer
- Intarder
- Rear underrun
- Kerb mirror: right
- Heated wide angle mirror

Interior

- Board computer
- Multifunctional leather steering wheel
- Digital tachograph
- Carpet floor covering
- Cooling box

Audio & communication

- Radio/CD
- AUX & USB connector

Light and sight

Tinted glass

- Headlight range control
- Daytime running lights

Wheels and tyres

Comfort

- Adjustable steering column
- Electric window lift 2x
- Automatic climate control
- Driver's armrest
- Comfortable driver seat
- Additional heating
- Central locking with remote control
- Air-suspended driver seat
- Isolated driver's cab
- DC/AC converter

Exterior

- Self-levelling suspension
- Electr. and heated rear view mirrors
- Low noise
- Rear differential lock
- Fifth wheel
- Lifting roof (manual)
- Telematics system

Assistance systems

- Cruise control
- MAN BrakeMatic
- Hill Hold Control HHC
- efficientroll
- Speed limiter

Equipment packages

- Aero package
- Efficientline 2 package

Spare wheel carrier

Others

front springs parabolic 7.5 t, rear air
suspension 13 t, hub reduction rear axle
Hypoid HY-1350, HY axle ratio i 2.71, fuel
filter heating, cab insulation NORDIC, wiring
for tank truck to ADR, ADR Typ AT,
equipment for dangerous goods to ADR, type
OX, supply kit for semitrailer with lifting axle or
moving-off aid, trailer socket 24V (7-7-pin),
pick-up plate 40 mm